



## Assmann Polyethylene Chemical Feed Stations— Compact, complete and ready to use



Primary tanks and containment basins are made of corrosion-resistant, FDA-compliant, virgin linear polyethylene (LMDPE).

**Assmann feed stations allow you to handle small amounts of liquids and other chemicals without the handling costs and inconvenient disposal of steel drums.**

- Lightweight, easy-to-handle
- Uniform wall thickness allows the entire surface to cure evenly for a stronger tank
- Air-cooled for a more uniform resin cure, reduced wall stress and improved shrinkage parameter for more consistent quality, greater structural integrity and longer life
- Primary tanks are semi-translucent
- Basins are capable of holding a minimum of 110% of the primary tank (Check local regulatory agencies for compliance in your area)
- 16" threaded lid with removable 6" air breather
- Easy-to-read volume markers



Optional polyethylene stands, which may be stacked 2-high, support the primary tank for gravity feed.



Polyethylene pump shelf supports most pumps and metering devices. Optional fiberglass shelves are available for pumps and metering devices totaling 25 pounds or more.



**Capacities from 40 gallons to 550 gallons**



Certificate Number:  
DAS 90024930/381Q

# Durable, reliable Assmann Polyethylene Chemical Feed Stations are designed with your convenience and the environment in mind

Customize an Assmann Polyethylene Chemical Feed Station to your needs with these and other options:

- Primary tanks in corrosion-resistant crosslinked polyethylene
- Primary and secondary containment tanks in many colors
- Fittings in a variety of sizes and materials to fit your requirements
- Adhesive-backed decals with your company name and logo

Contact Assmann today.  
Call, fax, e-mail or visit us  
on the internet.



Optional fitting assemblies include calibration cylinders, fill hoses with quick disconnect features, and manifolds.



Model Number	Capacity		Length	Width	Height	Primary Tank Access Openings
	US Gallons	Liters				
CFS 40	40	151	32	26	38	16
CFS 60	60	227	47	32	42	16
CFS 80	80	303	47	32	49	16
CFS 140	140	530	52	38	58	16
CFS 175	175	662	60	43	51	16
CFS 200	200	757	60	43	57	16
CFS 250	250	946	72	43	69	16
CFS 300	300	1136	72	43	82	16
CFS 550	550	2082	83	64	82	16

Model number availability and individual specifications subject to change without notice. Gallonage, weights approximate. All wall thicknesses conform to ASTM D-1998. Consult factory.

 **Assmann**<sup>®</sup>  
Assmann Corporation of America  
300 N. Taylor Road, Garrett, IN 46738  
Phone: 888-357-3181 • Fax: 888-Tank Fax (826-5329)  
Phone: 260-357-3181 • Fax: 260-357-3738  
**E-mail: info@assmann-usa.com**  
**Internet: www.assmann-usa.com**  
Manufacturing facilities in Garrett, IN and Marshall, TX

Authorized Distributor: