



ACCESSORIES			DEG	ELEV	DOME
MK	SIZE	DESCRIPTION			
A	11	THREADED ACCESS OPENING WITH GASKET (MANWAY)	0	-	X
B	1	BULKHEAD FITTING WITH GASKET, ANTI-FOAM ELBOW, CLOSE NIPPLES, UNION, BALLVALVE AND HOSE ASSEMBLY WITH FEMALE QUICK CONNECT AND DUST PLUG (FILL CONNECTION)	0	-	X
C	2	BULKHEAD FITTING WITH GASKET AND INTERNAL DROP TUBE ASSEMBLY WITH FOOTVALVE AND SCREEN (SUCTION)	90	-	X
D	3	BULKHEAD FITTING WITH GASKET AND POLYPRO MUSHROOM VENT WITH SCREEN (VENT)	SEE PRINT		X
E	2	BULKHEAD FITTING WITH GASKET AND THREADED PIPE PLUG (SPARE)	SEE PRINT		X
F	2	BULKHEAD FITTING WITH GASKET AND THREADED PIPE PLUG (SPARE)	SEE PRINT		X
G	2	BULKHEAD FITTING WITH GASKET AND THREADED PIPE PLUG (SPARE)	SEE PRINT		X
H	2	MILD STEEL EPOXY COATED 2 1/2" THICK GRATING	-	-	X

NOTES:
 1 MAXIMUM LOAD CAPACITY FOR THIS UNIT IS 4500 LBS. @ 3 1/2" HOUR INCREMENTS
 2 ASSEMBLY IS DESIGNED FOR INDOOR USE ONLY

REV	REVISION DESCRIPTION	REV DATE

 CORPORATION OF AMERICA	300 N TAYLOR ROAD GARRETT, IN 46738 PHONE: (260) 357-3181 FAX: (260) 357-3738	CUSTOMER APPROVAL 667 LBS.
TITLE BC 450 GAL. DOUBLEWALL UNIVERSAL BASE CONTAINER		DRAWN BY S WILLIAMS DWG NUMBER BC450-1 DATE 1/6/09

ALL DIMENSIONS ARE IN INCHES AND ARE ±3%