

NOTES:

1 16" MANWAY W/ LEVER LOCK COVER

2 28" x 43" MANWAY FLAT

3 11" X 11" DOME FLAT (TYP. 3 PLACES)

4 11" X 14" LOWER FLAT (TYP. 6 PLACES)

5 MOLDED IN VOLUME MARKER (25 GAL. INCREMENTS)

좆

SIZE

DESCRIPTION ACCESSORIES

DEG ELEV DOME

_											_	_	
		D. MYERS	DRAWN I		""" ICT 1100 gat.	TITE .	()	RE/	Α	
ALL DIMENSIONS ARE IN INCHES AND ARE +3%	ASSMANN CORPORATION	ERS	¥	\r \r \r	įΩ	1	SI SI			Ì			
		_	ם	JUL	1100		ORPOR.		7	•		. AI	
		4/8/03	RAWN DA	Ť			CORPORATION OF AMERICA					DED	
퉑	ANN -			,) 		DF AME				굕	VOLU	
z z	CIRP	APPROVAL	EMELS SID	AUE)		RICA	-	;		VISIC	ME ►	
뒑	JRAT1	#: 	æi æ	VEXTICAL VILXAGE TANK	+						N H	IARKE	
₽ T	뮏			7			FAX	PH വ	300		REVISION DESCRIPTION	ADDED VOLUME MARKER TO DRAWING. @ 330*	
							(260)	ARRET	N TAY		YII.	DRA	
۲.							FAX: (260) 357-3738 TANK DESIGNED SPECIFIC GRAVITY	GARRETT, IN 46738 POLYETHYLENE	300 N TAYLOR ROAD		_	WING.	
		Ļ		L		ل	738	738	ð	_		GD	l
(LOI	DWG NUMBER:	SOLOR	TANK	TANK WEIGHT		PER DES		' '	RESIN USED		330*	
-	-	E E				1		HY		Đ			
H	1100	اي						ENE ENE			쮸	8/1	
($\frac{1}{2}$				- LBS		SP.G				REV DATE	8/10/04dam	
-	⊳	RE V			S.		SP.G. MAX)TE	dam	