





- NOTES:

 1 7' ACCESS W/ THREADED LID AND RIM
 2 MOLDED IN PUMP SHELF
 3 PRIMARY CALCULATED GALLONS PER INCH: 6.21 GPI
 4 CALCULATED STRAIGHT SIDE CAPACITY: 150 GAL.
 5 SECONDARY CALCULATED GALLONS PER INCH: 7.35 GPI
 6 CALCULATED STRAIGHT SIDE CAPACITY: 212 GAL.

					₹	
					MK SIZE	
					DESCRIPTION	ACCESSORIES
					DEG	
	·	·	·	·	DEG ELEV DOME	
					DOME	

-18**3***-

180°

ALL DIMENSIONS ARE IN INCHES AND ARE ±3%	_	DOUBLE WALL STORAGE TANK	TOUR F WALL STORAGE TANK	- POLYI	RESIN USED					RE/	Þ	В
				PRIMARY VESSEL RESIN USED - POLYETHYLENE		CORPORATI		Ž			י מאואר די	
				TANK COLOR –	TANK VEIGHT	SPECIFIC GRAVITY	Asinului CORPORATION OF AMERICA		RE/	INSERTE	REVA	
					-LBS.	- SP.G. MAX				REVISION DESCRIPTION	INSERTED A NEW TITLE BLOCK	REVAMPED THE DIMENSIONS
0 ARE ±3%				- POLYETHYLENE	RESIN USED:	SECONDARY VESSEL	PHDNE: (260) 357-3181 DVERALL FAX: (260) 357-3738 TANK VEIGHT			RIPTION		
Ľ	J	DVG	DRAW D. C				TANKS.	§	2			-
-	<u>></u> 	DWG NUMBER	D. CRAGER	COLOR -	VEIGHT	SPECIFIC GRAVITY	VETIGHT	97E-5				1
(IMT 150	یہ	DRAWN DATE:		-LBS.	- SP.C	-LBS.			REV DATE	6/12/08 MG	6/12/08 MG
	ν V	RE V	/01		35.	SP.G. MAX	35.			ATE	징	ᄧ