


- NOTES:

 1 LOCATE FITTINGS FROM PLAN VIEW.
 2 TANK(S) MUST BE INSTALLED PER ASSMANN
 CORPORATION USAGE & GUIDELINES.
 3 FLEXIBLE EXPANSION JOINTS MUST BE USED
 ON ALL SIDEWALL CONNECTIONS.
 4 TANKS ARE BUILT PER ASTM D 1998.



REVISION DESCRIPTION													
RESIN USED T. IN 46738 POLYETHYLENE 9 357-3738 POLYETHYLENE 9 198-2738 POLYETHYLENE 1 19 SP.G. M. TAMA TAMA TOWG NUMBER: FED 1 8 5 PREV 1 18 5 PREV	ALL DIMENSIONS ARE IN INCHES AND ARE		2/27/13	DRAWN BY: DRAWN DATE: SALES DRDER#	OFFICENCE OF CENTALNMENT BAV.	OIDDINATE OF THE PROPERTY OF		•		300 N TAY			
PESIN USED POLLYETHYLENE POLLYETHYL	±3%				Z	-) 357-3736	T, IN 46738 D) 357-318 :	LOR ROAD		~	
ENE 47 LBS. M. 47 LBS. REV 185 REV.	ť		DWG NUMBE	COLOR	TANK	TANK WEIGHT	SECURIC GRAVE	TANK DESIGNED	POLYETHYL		RESIN USED		
SP.G. M. 7 LBS. 7 LBS.	18		ΣŪ			4		, 1.9	Ë			٧BA	
20 중						7 LBS		SP G				DΑ	
× ×	,	0	RE/			Ž,		X A X				Æ	