

Open Top Tanks



Our industrial open top (IOT) tanks are molded from your choice of virgin high-density cross-link or NSF-certified linear polyethylene. These flat bottom vertical tanks are molded with a stiffening lip on the top to give the tank rigidity, and they are equipped with a shoe-box style cover.

Assmann open top tank covers include a unique design that allows the lid to be hinged and stay open. They are available in a variety of colors and in sizes ranging from 30 to 680 gallons. We also offer both stainless steel and mild steel epoxy-coated agitator support stands.

Model Number	Capacity (US Gallons)	Dimensions (Inches)		Weight (Pounds) 1.9 Sp. Gravity		Access Opening (Inches)
		Diameter	Height	Linear Polyethylene	Crosslink Polyethylene	
IOT 30	30	19	30	18	18	Open top
IOT 40	40	18	41	27	27	Open top
IOT 55	55	22 ³ / ₈	37 ¹ / ₂	30	30	Open top
IOT 70	70	22	46	33	33	Open top
IOT 90	90	24	50	42	42	Open top
IOT 150	150	30	51	55	55	Open top
IOT 210	210	35	52	65	65	Open top
IOT 300	300	42	57	95	95	Open top
IOT 400	400	69	32	120	120	Open top
IOT 680	680	69	48	130	130	Open top

