

4		ω		N	$\vdash$	Z
4 TANKS ARE RIII I PER ASTM II 1998	ON ALL SIDEWALL CONNECTIONS.		CORPORATION USAGE & GUIDELINES.	TANK(S) MUST BE INSTALLED PER ASSMANN	1 LOCATE FITTINGS FROM PLAN VIEW.	NOTES:

В	RENAMED DRAWING FROM ICB600 TO OTCB600	500	6/5/17 SR	SR
Þ	UPDATED THE TITLE BLOCK		11/24/08 MG	₩.
RE۷	REVISION DESCRIPTION		REV DATE	)TE
		RESIN USED		
/				
	GARRETT, IN 46738 POLYETHYLENE PHONE: (260) 357-3181 POLYETHYLENE	יםר אבזאארו.	ENE	
(	CORPORATION OF AMERICA FAX: (260) 357-3738 TANK DESIGNED SPECIFIC GRAVITY	ANK DESIGNED PECIFIC GRAVITY	- SP.G. MAX	MAX
I(	""" ICB 600 GAL, CONICAL	TANK	- LBS.	Ϋ́
В	BOTTOM STORAGE TANK	TANK		
D. CRAGER	AGER 08/13/98 SALES DEDER#	DWG NUMBER		RE <
	ASSMANN CORPORATION OF AMERICA	TTCR KNN	000	IJ
₽	ALL DIMENSIONS ARE IN INCHES AND ARE ±3%	- (		ţ

				Þ	좆	
				-	SIZE	
				OPEN TOP COVER		ACCESSORIES
				-	DEG	
				1	ELEV	
				×	DOME	
					- OPEN TOP COVER	SIZE DESCRIPTION DEG ELEV DI - OPEN TOP COVER